

User administration

- [Add new user, set password and grant permissions](#)
- [Reset root password](#)

Add new user, set password and grant permissions

```
CREATE USER 'novousuario'@'localhost' IDENTIFIED BY 'password';  
GRANT ALL PRIVILEGES ON * . * TO 'novousuario'@'localhost';  
FLUSH PRIVILEGES;
```

```
CREATE DATABASE nome_da_base_de_dados;
```

```
CREATE USER 'nome_do_usuario'@'localhost' IDENTIFIED BY 'senha';  
GRANT ALL PRIVILEGES ON nome_da_base_de_dados.* TO 'nome_do_usuario'@'localhost';  
FLUSH PRIVILEGES;
```

Para alterar a password:

```
ALTER USER 'usuario'@'host' IDENTIFIED BY 'nova_senha';  
FLUSH PRIVILEGES;
```

Se o MySQL estiver em uma versão anterior a 5.7.6, o comando seria:

```
SET PASSWORD FOR 'usuario'@'host' = PASSWORD('nova_senha');
```

Reset root password

```
sudo /etc/init.d/mysql stop  
sudo /etc/init.d/mysql status  
sudo mysqld_safe --skip-grant-tables &  
mysql -u root
```

```
use mysql;  
update user set password=PASSWORD("mynewpassword") where User='root';  
flush privileges;  
exit
```

```
sudo /etc/init.d/mysql stop  
sudo /etc/init.d/mysql status  
sudo /etc/init.d/mysql start  
sudo /etc/init.d/mysql status
```

<https://support.rackspace.com/how-to/mysql-resetting-a-lost-mysql-root-password/>